

Muralo Universal Primer Sealer 2205

Special Features:	<ul style="list-style-type: none"> •A 100% acrylic VOC compliant interior –exterior, stain killing <u>primer-sealer</u>. •Outstanding adhesion to hard and glossy surfaces •Eliminates need for sanding or deglossing •Blocks most household stains, environmentally safe, spatter-resistant •High hiding •Fast Drying
Recommended Uses:	For interior and exterior use on previously painted or unpainted wood, aluminum, plaster, concrete and masonry, drywall, galvanized metal, tile Formica®, and glass.
Surface Preparation:	All surfaces must be clean and free from dirt, dust, grease, oil, peeling paint and mildew. A white powdery deposit (efflorescence) often found on masonry surfaces should be completely removed with a stiff wire brush.
Application:	<p>Can apply by brush, roller, or spray. For best results use a synthetic bristle or mixed nylon and natural bristle brush.</p> <p>Roller: 3/8 to 1/2 inch nap gives best results</p> <p>Sprayer: An 8 to 12 inch fan at 1 foot is ideal for airless and can be obtained with a tip size from .018 to .021 inches. Conventional spray, best results are obtained with air nozzle orifice sizes from .04 to .07 inches and pressures from 30 to 70 psi. Fluid nozzle orifice size should be .07 to .11 inches.</p>
Specification:	<p><u>Wood, Non-Staining New or Unpainted:</u> Primer: Spot prime all knots with Muralo's Muralock #563, follow with one full coat of Muralo #2205, Universal Primer Sealer. For staining woods such as cedar and redwood use Muralo #2201 Finish: 1 or 2 coats appropriate Muralo finish paint</p> <p><u>Wood Previously Painted:</u> Primer: Muralo #2205, Universal Primer Sealer Finish: 1 or 2 coats appropriate Muralo finish paint.</p> <p><u>Ferrous metal, New, unpainted or rusty:</u> Primer: Use Muralo Anti-Rust Primers Finish: 1 or 2 coats appropriate Muralo finish paint</p> <p><u>Ferrous metal, previously painted but not rusted:</u> Primer: Muralo #2205, Universal Primer Sealer Finish: 1 or 2 coats appropriate Muralo finish paint</p>

Revised 3/5/2005

Specification Cont.:	<p><u>Drywall, plaster or masonry, painted or unpainted:</u> Primer: Muralo #2205, Universal Primer Sealer Finish: 1 or 2 coats appropriate Muralo finish paint</p> <p><u>Aluminum or galvanized metal: Painted or unpainted:</u> (Note New galvanized metal should be allowed to weather for 6 months prior to coating) Primer: Muralo #2205, Universal Primer Sealer Finish: 1 or 2 coats appropriate Muralo finish paint</p>
Coverage:	Approximately 400 sq. ft. per gallon
Dry Time:	(75°F., 50%RH) To touch 1 hour; To recoat 2 hours
Thinning:	Not recommended.
V.O.C. (V.O.S.)	Max. 200 gms./ltr. Or 1.67 lbs/gal.
Packaging:	Quart, gallon and five gallon containers
Colors:	White. May be tinted with up to 4 ounces of universal colorant per gallon
Generic Type:	Acrylic-Latex
Finish:	Eggshell
Weight Per Gallon:	12 pounds
Solids Content:	By volume 41% By Weight 54%
Recommended Film Thickness:	Wet: 3.5 – Mils Dry: 1.5 Mils
Cautions:	Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing. Do not apply when temperature is below 40°F.

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.