

**Muralo Lumber Jacket Oil Based Solid Color Siding Stain Flat Finish**  
**1600 Line****Description:**

Muralo Lumber Jacket Oil Based Solid Color Siding Stain is the “Ultimate” in exterior based stains. Its linseed oil based formula offers maximum color retention; superb adhesion and a water-resistant finish which protects wood from warping and checking. Muralo Lumber Jacket Oil Based Color Siding Stain applies easily and is formulated to minimize lapping. It is available in many natural or popular ready-mixed and custom-tinted colors.

**Recommended  
Uses:**

New or properly prepared previously stained; shingles, shakes, clapboards, hardboard and plywood siding.

**Surface  
Preparation:**

The surface to be coated must be clean, firm, completely dry and free from all dirt, dust, grease, oil and wax. Certain types of siding can develop mill glaze; a hard shiny coating that results from processing the wood. If your new wood surface exhibits this look and shininess, hand sanding or chemical cleaning may be required to remove it. Please consult your Muralo Dealer for the proper procedure. Muralo Lumber Jacket Oil Based Solid Color Siding Stain is not recommended for use over surfaces previously coated with silicone based paints or stains unless they have weathered for a period of 2 years. Preparing under eaves and other protected areas: these areas do not receive cleaning from the natural elements of rain and wind. The best way to clean such surfaces is to power or brush wash with a conventional detergent followed by a rinse of clean water.

**Mildew Removal**

Prepare a solution of 1 quart of liquid household bleach and 3 quarts of water.

Leave the solution on the surface for about 10 minutes. Rinse thoroughly; allow the surface to dry thoroughly before applying stain. Be sure to wear protective goggles, waterproof gloves and protective clothing while working with this solutions. Wash off any solution that comes in contact with skin immediately. Do not add any detergents or ammonia to the bleach/water solution.

**Application:**

Must be thoroughly dry before staining “green” or unseasoned lumber should be allowed to weather for 30 days before staining. If mildew is present follow the instructions for mildew removal as shown in the mildew removal section of this label.

Mix thoroughly before using. Stir occasionally during application. For best results “box” different batch numbers of the stain into a common container. Apply with brush, roller, pad or spray equipment. Apply liberally and consistency, avoiding “lap” marks by always maintaining a wet edge between staining and unstained areas. Clean hands, tools and equipment with mineral spirits or turpentine.

**Spray:**

Airless - Tip size .048 - .021 @ 200 #psi

Conventional – Adjustments: .040 - .110 @ 5” fan pattern

Revised 2/2/2004



<b>Colors:</b>	10 premixed colors and 3 tint bases
<b>Package Sizes:</b>	5 Gallons, Gallons
<b>Coverage:</b>	400 sq. ft. per gallon on average depending upon porosity of surface
<b>Dry Time:</b>	To touch 6-8 hours; to recoat 24 hours
<b>V.O.C.:</b>	Contains max. 3800 gms./ltr. Or 3.2 gal.
<b>Weight Per Gal:</b>	11.5 lbs per gallon
<b>Viscosity:</b>	65-70 KU
<b>Flash Point:</b>	110°F – Closed Cup
<b>Pigment/Vehicle:</b>	Pigment: 45.0 to 51.0 Vehicle: 55.0 to 49.0
<b>Features &amp; Benefits:</b>	<ul style="list-style-type: none"> <li>•Proprietary Linseed oil based resin system</li> <li>•Provides easy application, deep penetration and long lasting protection</li> <li>•Available in a broad range of ready-mixed colors</li> <li>•These ready to go popular colors are great for ease of preparation and application</li> <li>•Adheres to both oil base and latex stains</li> <li>•No need to determine what was used the last time the surface was stained</li> </ul>
<b>Thinning &amp; Clean Up:</b>	<p>Muralo Lumber Jacket Solid Color Oil Base Stain is formulated for use directly from the container. DO NOT THIN. Clean equipment with Mineral Spirits.</p> <p><b>Use Completely or Dispose of Properly</b></p> <p>Save unused product for touch up purposes or household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. <b>Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for information on disposal.</b></p>
<b>Caution:</b>	<p><b>KEEP OUT OF REACH OF CHILDREN</b></p> <p>Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing. Do not apply when temperature is below 50° F.</p>

## **DISCLAIMER:**

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

**NOTICE:** Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.