

Muralo Lumber Jacket Clear & Natural Transparent Deck & Siding Stain
2700 Line

Description:	Muralo Lumber Jacket Clear & Natural Transparent Deck & Siding Stain is specially formulated with Tung Oil Resins and the finest sun blocking pigments available giving maximum protection to decks, siding, railings and trim without masking the natural beauty of the wood grain. The product is designed to inhibit mildew growth on new wood surfaces and block harmful UV rays that cause sun damage.
Recommended Uses:	Recommended for use on surfaces such as: decks, siding, fences, railings and outdoor furniture.
Surface Preparation:	<p>Lumber Jacket Clear & Natural is not intended for use over previously sealed surfaces. Any surface that has been previously stained or sealed must be thoroughly cleaned with the recommended cleaner or remover. Allow new wood that has not been kiln dried to season or dry before staining. Dry time will vary depending on weather and moisture content or wood. Several weeks of warm dry weather is usually sufficient.</p> <p>It is important to check for the presence of mill glaze on any new wood surface. Mill glaze is a clear hard coating left on wood surface resulting from its final processing. To ensure that coatings adhere to such woods, mill glaze must be removed either by sanding or chemical remover. Please consult your Muralo Dealer for mill glaze removal advice. Be sure to remove dirt debris from all surfaces that are to be stained and do not apply Lumber Jacket Clear & Natural to wet or damp surfaces.</p>
Application:	<p>Before use, thoroughly mix the contents of the can. Stir occasionally during use to keep color uniform. Check for different batch numbers (See numbers on the lid of the can) if the numbers are not the same, it is recommended that different batches intended for use on the same surface be “boxed” into a common container. Doing so will ensure that the stain from different batch lots will combine into a uniformly shaded batch.</p> <p>Before starting the entire job, be sure to apply a test application of the stain to an inconspicuous area of the job. Because all woods accept stains differently the color of the stain when applied can differ slightly from the merchandising samples. Allow your test panel to dry before determining what the final stain color will look like.</p> <p>Apply by brush, roller or spraying. Brushing with a natural bristle brush is the best way to uniformly apply the stain. Should rolling or spraying be required be sure to avoid over – applying the stain which would result in uneven accumulation on the surface. Should this occur, dry rolling such areas will redistribute the stain more evenly. Dry rolling must be completed before the stain has begun to dry.</p> <p><u>Application temperature:</u> Do not apply Lumber Jacket Clear & Natural at temperatures below 40°F. Avoid staining in direct sunlight to inhibit premature drying and lapping of the stain.</p>

Revised 3/5/2005

Colors:	5 Ready Mixed Colors*
Package Sizes:	Gallons
Coverage:	200 to 400 sq. ft. per gallon on average depending upon porosity of surface
Dry Time:	Lumber Jacket Clear & Natural Deck & Siding Stain requires 8 hours to dry to touch and 24 hours to return a deck to service. These times can vary depending upon temperature and humidity. Cooler temperatures and high humidity will lengthen these times. To ensure that the stain has properly dried, it is best to check by touching the film to test for any tack or stickiness. If after the recommended 24 hours drying time no stickiness is detected then the stained surface can be returned to service.
V.O.C.:	Contains max. 250 gms./ltr. Or 2.10 gal.
Weight Per Gal:	7.0 +/- 0.2 lbs per gallon
Viscosity:	45 seconds (#2 Zahn Cup)
Flash Point:	101°F – Closed Cup
Features & Benefits:	<ul style="list-style-type: none"> •Tung oil and Transoxide Pigments •Provide maximum weather and scuff resistance •Special resins penetrate deeply into wood surface •Wood's natural beauty is enhanced and protected •Available in Natural and Wood Tone Colors •Provides subtle wood coloring while enhancing wood grain features •Unique "Transparent" hue •Will not mask woods texture
Thinning & Clean Up:	<p>Thinning not recommended. Clean up with Mineral Spirits or turpentine.</p> <p>Use Completely or Dispose of Properly</p> <p>Save unused product for touch up purposes or household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for information on disposal.</p>
Caution:	<p>KEEP OUT OF REACH OF CHILDREN</p> <p>COMBUSTIBLE!!!!</p> <p>Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing. Do not apply when temperature is below 50° F.</p> <p><i>*Coastal Gray #2754 is semi-transparent in appearance due to its pigment content.</i></p>

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.