

Muralo 100% Acrylic Quik-Tred Latex Floor and Patio Paint M0100

Description:

Quik-Tred is a fast drying Acrylic Latex Floor Paint especially designed for use on interior and exterior surfaces. The tough, durable latex film dries to a medium gloss finish and can be walked upon in about 1 to 2 hours after painting. Its excellent adhesion, toughness and resistance to alkalinity makes this an ideal all purpose floor finish for all substrates. Recommended for areas where safety (ignitable fumes) and rapid dry are major considerations, and for concrete floors where dusting is a problem. Permits installation of tile and other floor covering materials directly over it.

**Recommended
Uses:**

Ideal for inside or outside application over new or old wood and masonry surfaces such as patios, cellar floors, playrooms, porches, stairways, etc.

**Surface
Preparation:**

All surfaces must be clean and free from dirt, dust, grease, oil or peeling paint. A white powdery deposit (efflorescence) often found on masonry surfaces, should be completely removed with a stiff wire brush. All glossy surfaces should be lightly sanded and cleaned before painting.

Not Recommended for concrete driveways and garage floors.

New or unpainted surfaces: No priming is required for new or unpainted surfaces in sound condition. New or old unpainted concrete surfaces frequently exhibit a fine dust of cement particles that result from a dry-out on the surface as the concrete sets. This condition must be treated like efflorescence as mentioned above.

Previously Painted Surfaces: No priming is necessary unless the surface is chalking or deteriorating. Such surfaces must be thoroughly cleaned and primed with an alkyl primer. Dull all smooth and glossy surfaces by sanding lightly.

Application:

For best results, use;

Brush: Synthetic or nylon bristled brush

Roller: ¼" nap roller cover for smooth surfaces, and 3/8" to ½" nap roller for rough surfaces

Spray: A tip size from 0.018 to 0.021 inches, and atomizing pressure required to maintain a 8" to 10" fan at 1 foot distance. For conventional spray, use 0.028" to 0.07" fluid nozzle with air pressure to give 6" to 12" spray pattern at 8" to 12" distance.

Finish:

Medium Gloss 60°Gloss = 20 to 30

Colors:

Premixed colors plus black & white

Revised 2/2/2004

Viscosity:	80 – 90 ku									
Weight per Gallon:	9.7 + 0.2 lbs per gallon									
Coverage:	One coat is usually sufficient									
Spreading Rate:	400– 450 sq. ft. per gallon over most surfaces. Less on rough and textured surfaces									
Dry Time:	Dries in 1 to 2 hours under normal conditions. High humidity and low temperature will prolong dry time. Can be recoated in 2-3 hours.									
Thinning:	Not recommended. If necessary, thin sparingly with clean water									
Flash Point:	Water based paint									
Freeze-thaw:	Passes three cycles									
V.O.C. (V.O.S.)	Contains max 250 gms./ltr. Or 2.1 lbs./gal VOC									
Fire retardant Rating:	N.F.P.A. class “A” when tested on non-combustible substrates									
Formulation:	<p>Pigment* 40.0 – 50.0%</p> <p> Titanium Dioxide</p> <p> Calcium Carbonate</p> <p> Organic and Inorganic colored pigments</p> <p>Vehicle* 50.0 – 60.0%</p> <p> Acrylic Resin</p> <p> Alcohols, Glycols and Esters</p> <p> Water</p> <p>*The analysis shown gives the range of pigment and vehicle content of various colors. Type of pigment and vehicle components may vary according to color selected</p>									
Packaging:	<table><tr><td></td><td>Per Case</td><td>Aprox. Wgt.</td></tr><tr><td>Gallons</td><td>4</td><td>45 lbs.</td></tr><tr><td>Quarts</td><td>6</td><td>19 lbs.</td></tr></table>		Per Case	Aprox. Wgt.	Gallons	4	45 lbs.	Quarts	6	19 lbs.
	Per Case	Aprox. Wgt.								
Gallons	4	45 lbs.								
Quarts	6	19 lbs.								
Cautions:	Keep out of reach of children. Keep away from heat and flame. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from Freezing. Do not apply when temperature is below 50°F									

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.