

Muralo Adhesium 8060 Heavy Duty Clear Vinyl Paste

Description:

Adhesium 8060 is a high solids ready to use clear vinyl adhesive specially designed for the installation of all types of heavy duty and commercial weight wallcoverings. 8060 has excellent tack, superior holding power and dries clear so that even the most delicate wallcovering can be safely installed without danger of staining. Preferred by both professionals and amateurs because it is easy to use, hold seams tight, odorless, non-staining, non-flammable and mildew resistant. Clean up with water.

Recommended Uses:

Can be used to hang all types of wallcovering including commercial weight vinyls or mylars, light and medium vinyl and foils, machine printed wallpaper, hand prints, screen prints, murals, grass cloths and paper backed fabric laminates.

Surface Preparation:

Clean surface to be wallpapered and make sure it is free of all contaminants, including mildew. Fill and repair cracks or holes with Muralo Spackle[®] brand of surfacing compound or Synkoloid's Spackling Paste. Glossy surface should be dulled and given a coat of 8400 Adhesium Vinyl Primer or 8500 Oil Base Primer.

Previously painted flat should be given a coat of 8400 Vinyl Primer or 8500 Oil Base Primer to insure adhesion.

Unpainted wallboard should be given a coat of 8500 Oil Base Primer to insure subsequent release. Previously hung vinyl wallcovering that is firmly bonded should be coated with Adhesium 8400 Vinyl Primer.

Application:

Follow wallcovering manufacturers instructions and good paper hanging methods. Use paste as is.

Apply paste in a uniform manner, making sure no dry spots are left. Use a brush or a medium nap (3/8") roller. Remove all excess adhesive from the face of the wallcovering with clear water and sponge. Temperature should be at least 50°F when applied. Keep adhesive tightly sealed when not in use. Store between 60°F to 80°F for easiest application.

Open Time:

30 minutes to one hour depending upon porosity of wallcovering, condition of wall, temperature and other variables

Weight/Gal:

8.9 + 0.1

Revised 2/2/2004

Viscosity:	85 ku's (paste paddle)	
Freeze Thaw:	Protect from freezing	
Color:	Dries Clear	
Solids:	22 23% by weight	
Flash point:	None to boil	
Clean-UP:	Soap and water	
Coverage:	Approximately 200 sq. ft. per gallon or 6 to 8 rolls	
Packaging:	Per Case	Weight
	Quarts	6 16 lbs
	½ Gallons	6 32 lbs.
	Gallons	4 41 lbs.
	2 Gallons	Pail 21 lbs.
	5 Gallons	Pail 52 lbs.
VOC/VOS:	Contains 2.7 lbs./gal. VOS or 335 gms/ltr. VOC	
Cautions:	Keep out of reach of children. Do not take internally. Use adequate ventilation. Keep from freezing.	

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.