

Muralo Adhesium 8400 Vinyl Wallcovering Primer

Description:	A truly universal vinyl primer that prepares all surfaces for wallcoverings. 8400 dries fast to a transparent clear finish so that it will not discolor adjacent areas. It helps to improve adhesion of wallcoverings to slick surfaces such as glossy enamels, tiles, Formica, glass and previously hung vinyl in sound condition. It seals porous surfaces and prevents premature water loss, thereby extending open time and improving workability of all types of adhesives including prepasted wallcoverings.
Recommended Uses:	<ul style="list-style-type: none">•Under all wallcoverings, unpasted or prepasted without exception•Over porous surfaces such as plaster, sheetrock and wallboard•Over glossy surfaces such as enamel, lacquer, glass, Formica, tile•Over previously hung vinyls and other wallcoverings
Surface Preparation:	<p>Clean the surfaces before application to be sure it is dry and free of dirt, mildew and other contaminants</p> <p>Glossy surfaces should be dulled by sandpapering to maximize adhesion</p> <p>Previously hung wallcoverings must be clean and tightly bonded to surface</p>
Application:	Apply with brush, roller or pad. Stir thoroughly before use and occasionally during use. Do not mix with other paint or thinner. If two coats are necessary allow the first coat to dry two hours. Temperature of the surface should be at least 50°F when applied.
Appearance:	Dries to a transparent clear finish
Drying Time:	30/60 minutes depending upon spreading rate and ambient conditions
Coverage:	Up to 600 sq. ft. per gallon depending on porosity of the surface of the same area as 20 single rolls of wallcovering
Viscosity:	70-75 ku
Weight Per Gallon:	9.83 – 10.0 lbs.

Revised 3/5/2005

Formulation:

Pigment = 6.9%
 Silicates.....6.9%

Vehicle = 93.1%
 Vinyl Acrylic Resin.....12.0%
 Glycol Ethers.....2.4%
 Additives.....2.0%
 Volatile (water).....76.7%
 100.0%

Fire Retardant Rating:

N.F.P.A. Class "A" when tested on non-combustible substrates

V.O.C.(V.O.S.):

Contains Max. 200 gms./ltr. Or 1.67 lbs./gal. VOC

Packaging:

	Per Case	Weight
Quarts	6	16 lbs.
½ Gallons	6	30 lbs.
Gallons	4	40 lbs.

Cautions:

Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing. Do not apply when temperature is below 50°F

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.