

Muralo 681 Interior Ready Mixed Spackle[®]

Description:	Muralo Spackle is the finest quality ready to use surfacing compound designed for filling and repairing surface imperfections prior to painting or wallpapering. It dries fast and hard to a smooth paintable surface. It adheres well, sands easily and has excellent workability accentuated by long open time. It can be applied to a feather edge. An ideal product for smoothing large, uneven and alligatored surfaces.
Recommended Uses:	For interior use in filling holes, cracks, dents and gouge on plaster, wallboard, wood, masonry and painted metal.
Surface Preparation:	Clean surface thoroughly. Remove all loose dirt, paint, plaster, wax, grease and dust. Lightly sand glossy surfaces. Large holes in plaster should be filled with Patching Plaster; in masonry with hydraulic cement. Then bring to a smooth finish with Spackle [®] before painting.
Priming:	No priming is necessary except for rust-prone metals.
Application:	Apply with a putty knife (wide or narrow, depending on the size of the area being filled). Spread paste evenly, pressing into holes and cracks, and feathering out the edges. Deep cracks and holes may require more than one application. Allow 30 minutes between applications Paint over Spackle after 1 hour, except when applied heavily or when more than one application is necessary. Sand when dry to a feather edge if necessary prior to painting. Primer is recommended for all paints except for Latex Flat. Use recommended primer for the desired finish.
Clean Up:	Soap and water
Weight/Gal:	13.5 lbs.
Color:	White
Viscosity:	Smooth Paste
Dry Time:	Varies with film thickness, temperature and humidity. Under normal conditions (70°F, 50% RH) thin applications will dry in 10 – 15 minutes while thicker films dry accordingly.
Flash Point:	None (closed cup)

Revised 2/2/2004

Solids by Weight: 73.6%

Packaging:	Per Case	Weight
½ Pint	12	12 lbs.
Quarts	6	22 lbs.
Gallons	4	59 lbs.

Cautions: Keep out of reach of children. Keep from freezing. Do not apply in temperatures below 45°F. Do not take internally. Close container after each use.

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.

Spackle® is a registered trademark of the Muralo Company